P52

Discover the pleasure of performance



- Unique parallel movement
- Runs on low oil flow, 60-65% less than a traditional crane
- Easy to control, the crane tip moves in a straight line

Crane P52

FTG Källefall crane P52 provides a total reach up to 5.2 m and a 450 kg lifting capacity at the max reach.

Unique parallel movement that maintains the same lifting moment throughout the range. Only one cylinder is active for this movement.

Runs on low oil flow, 60–65% less than a traditional crane. This makes it possible to reduce the number of revolutions and improve fuel consumption and the environment.

Crane P52 comes standard with 3 ton rotator, FB160 grapple, rotator link without pending brake, mechanical control, 4 cylinder slewing motor. The forest crane has a

lifting moment of 28 kNm (gross) and a slewing torque of 8.5 kNm. There are numerous valve packages and accessories to choose from. Crane designed for versatile work applications:

- Forest trailers
- Chippers
- Log splitters
- Attachment to the tractor

P52 combined with FTG Källefall forest trailers offers high reliability and efficiency. Demand for maintenance is quite low for high-quality components and tested designs

Suitable trailers:

- FB70


Technical characteristics


Crane (standard equipment)

Parameter	P52	Parameter	P52
Reach, m Linkage system Telescope extension, m Lifting moment (gross), kNm Lifting moment (Net), kNm Lifting capacity at max reach, kg Lifting capacity at 4m, kg Slew torque, kNm	5,2 Yes - 28 23 450 550 8,5	Slewing angle, ° Total weight, kg Oil flow, l/min Rotator, type Rotator link, type Grapple, type Valve block, type Working pressure, bar	360 520 20-25 3 t Without pending brake FB160 Mechanical (2-Lev. / 3-Coord.)

▲FTG | KÄLLEFALL

Technical drawings





P52 accessories

Control system

Mechanical FRV60/8-E, 2 x El. On/Off



Mechanical 2-Lever, Lightweight, 4 x El. On/Off



Prehydraulic FRV60EO with Joysticks



Full electric with with ERGO-DigiStick® Joysticks



Radio control Scanreco®



Winch

1410 KPL with remote control



3-P attachment

A-frame type, CAT. I



Independent hydr. system for 3-P attachment



Block valve for telescopic support legs



Grapple

Grapple FB120 (0.12 m2)



Brush grapple FB160S (0.16 m2)



Round bale attachment for grapple FB160



Add-on bucket for grapple



Bucket-grapple KG180 (0.11 m3)



Other accessories

Chainsaw holder



LED work light on crane boom



LED work light on crane pillar



Supply pressure monometer



Connection of hydr. hoses on pillar



Shut-off valve for lifting cylinder



Valve block cover





FTG BALTIC UAB

Dūmų st. 3 K20 LT-11119 Vilnius, Lithuania +370 5 246 23 18 sales.vilnius@ftgforest.com By combining our Swedish heritage with constant innovation based on the needs of customers, we design forest trailers and cranes that impress by their consistently pleasant performance.

FTG Källefall forest trailers can pass through challenging terrains and are robustly built to withstand tough conditions in the forest. Trailers' capacity varies from 2,5 to 12 tones. Our trailers can be supplemented with telescopic cranes, ranging from 4,2 to 9,4 meters reach. Källefall cranes are strong, fast, and easy to operate. We also offer a wide range of timber grapples and other accessories to meet different needs.